




 MONTH, YEAR(MM, YYYY)
 CHINA

NOTES:

- | | |
|--|-------------------|
| 1. Creepage Distance | 5" (127mm) MIN |
| 2. Dry Arcing Distance | 3-3/8" (86mm) MIN |
| 3. Cantilever Strength | 2500lbs (11kN) |
| 4. Low Frequency Flashover Voltage (Dry) | 45kV |
| 6. Low Frequency Flashover Voltage (Wet) | 25kV |
| 7. Positive Critical Impulse Flashover Voltage | 70kV |
| 8. Negative Critical Impulse Flashover Voltage | 85kV |
| 9. Low Frequency Puncture Voltage | 70kV |
| 10. Radio Influence Voltage at 5kV | 50 microvolts MAX |
| 12. Color: Grey | |
| 13. Applicable Standard ANSI C29.5-1984 | |

GENERAL TOLERANCE			DP 55-2 PIN INSULATOR (ANSI 55-2 RADIO FREE GLAZE)					
<30 mm	±1.5 mm	ANGLE:		DULHUNTY POWER	Mass		Scale	
>30 mm	±5%				A4-6193	REV	A	
Drawn	Benny Chen	Dec.27,2006						
Checked	David Shao	Dec.27,2006						
Approved								