



Note

- |  |                           |
|--|---------------------------|
| 1. Creepage Distance                               | 24''(610 mm)              |
| 2. Cantilever Strength                             | 2,000lbs(8.9 kN)          |
| 3. Torsion Strength                                | 8000 inch-pounds(904 N-m) |
| 4. Tension Strength                                | 10,000lbs(44.5 kN)        |
| 5. Compression Strength                            | 10,000lbs(44.5 kN)        |
| 6. Critical Impulse Flashover Voltage(Pos.)        | 170 kV                    |
| 7. Low Frequency Withstand Voltage(Wet):           | 60 kV                     |
| 8. Impulse Withstand Voltage;                      | 150 kV                    |
| 9. Radio Influence Voltage at 15kV                 | 100 microvolts            |
| 10. Color: gray                                    |                           |
| 11. According to Standard Specification: ANSI 29.9 |                           |

General Tolerance			DP208 SOLID-CORE STATION POST INSULATOR (ANSI TR-208)					
<30mm	±1.5mm	ANGLE: ±		<b>DULHUNTY POWER</b>	Mass		Scale	N/S
>30mm	±5%				A4-6113	REV	B	
X.XX	±							
Drawing	William Ma	May 10,06						
Check	David Shao	May 10,06						
Approved								